

Version List for DER-CAM

Only the most recent versions of DER-CAM are shown and described below.

Legend for table:

<u>I&P:</u> Investment and Planning version: determines optimal equipment combination and operation based on *historic* load data, weather, and tariffs

<u>O:</u> Operations version: determines optimal multi-day-ahead scheduling for installed equipment and *forecasted* loads, weather and tariffs

<u>web:</u> free available academic and non-commercial version with limited features, access at http://der.lbl.gov/der-cam/how-access-der-cam/det: deterministic version, all data is assumed to be known perfectly

<u>stoch:</u> stochastic version in which some input data can be specified as scenarios and is used in stochastic programming

<u>research:</u> research license which needs a collaboration license agreement

General and simple DER-CAM presentation can be found at: http://der.lbl.gov/sites/der.lbl.gov/files/rpt81431.PDF.

An overview about DER-CAM and microgrid research can be found at: http://der.lbl.gov/sites/der.lbl.gov/sites/der.lbl.gov/files/microgrid_research_high_res_2013Dec18e.pdf.

The video http://www.nrel.gov/esi/seminar_economic_and_environmental_optimization_of_microgrids.html, presented at NREL on 28 March 2013 as part of the Energy Systems Integration Seminar Series, discusses some of our current projects and the results of various case studies.

Contact: Dr. Michael Stadler, MStadler@lbl.gov

comm: non-exclusive commercial license is available

Version Number	Characteristic	Public Release Date	Accessibility	Uncertainty	Features	Publication
3.9.4	I&P	24 April 2012	research / comm	det	 36 load profiles characterizing a year (week, weekend, peak profiles for every month) optimizes one typical year based on the 36 load profiles 5 load profile types: electricity only, cooling, refrigeration, heating, domestic hot water, and natural gas only only natural gas as energy carrier for combined heat and power (CHP) CHP, electric and heat storage, PV, solar thermal, absorption cooling, heat pumps, basic load shifting, basic efficiency measures, electric vehicles; fuel cell run-time constraint to model SOFC and PEM fuel cells multi-objective (costs and CO₂) policy measures as feed-in tariffs or Self Generation Incentive Program in California allows to force technologies into the solution electricity sales ZNEB and ZCB 	http://der.lbl.gov/public ations/electric-storage-californias-commercial-buildings http://der.lbl.gov/sites/der.lbl.gov/files/LBNL-4929E.pdf http://der.lbl.gov/public ations/web-based-economic-environmental-optimization-microgrids
3.9.4a	I&P		research / comm	det	© based on 3.9.4 from above, but with California Peak Day Pricing modeled	http://der.lbl.gov/sites/der.lbl.gov/files/LBNL-6267E_0.pdf
3.9.4.d	I&P	Summer 2014	research	det	based on 3.9.4, butwith district heating and GIS capabilities	
WebOpt version 2.4.0.24	I&P	June 2013	web / academic	det	 based on 3.9.4 from above without electric vehicles without policy measures as feed-in tariffs or Self Generation Incentive Program in California without electricity sales no technologies can be forced without ZNEB and ZCB with load profile database for ASHRAE 	http://der.lbl.gov/der-cam/how-access-der-cam

					Climata zanaa (760 h.:ildinaa in tha LIO)	
					Climate zones (762 buildings in the US)	
					© automatic multi-objective frontier feature	
			. ,		© Chinese and English version available	
WebOpt	I&P	January	web /	det	based on WebOpt version 2.4.0.24, but	
version		2014	academic			
2.5.1.26					© continuous technologies (PV, storage, etc.)	
					can be forced into the solution	
					© advanced user management that allows	
					private web-server space for WebOpt files	
					with PV solar radiation database for the	
					whole US	
					© extended manual with search feature	
4.0.0	I&P	July 2013	research/	det	© based on 3.9.4 from above	http://der.lbl.gov/sites/
			comm		© with cold storage	der.lbl.gov/files/LBNL-
					© with passive measure (window change,	6305E-Poster.pdf
					building shell upgrades)	☐ Journal papers for
					passive measures influencing heating and	passive measures and
					cooling loads	multi temperature heat
					© multi temperature heat storage (65C and	storage are
					95C)	forthcoming, more
					© multi-energy carrier for distributed energy	information via email
					resources and heating	to MStadler@lbl.gov
4.1.1	I&P	Dec 2013	research/	det	© based on 4.0.0 from above, but	Journal paper in
4.1.1	ΙαΓ	Dec 2013	comm	uei	© with non-linear efficiency curve modelling	preparation, more
			COITIII		for CHP systems, linearization with Special	information via email
3.9.4.m	I&P	Oct	roccorob/	det	Order-Set and binary variables © based on 3.9.4 from above, but investment	to MStadler@lbl.gov
3.9.4.111	ΙάΡ	Oct.	research/	aei		Journal paper in
		2013	comm		decision modelling	preparation, more
					 with multiple year optimization horizon 	information via email
					which	to MStadler@lbl.gov
					optimizes building total energy cost over	
					several years (the number of years is a	
					set that can be modified by the user)	
					 has an option that does/does not renew 	
					investments (same technologies, same	
					capacities) in installed technologies	
					after the lifetime is reached	
					with linear model for battery degradation	
					(i.e. capacity loss due to ageing)	
3.10.5.m	I&P	February.	research	det	© based on 3.9.4.m from above, but	Journal paper in
		2014			© with PV degradation model	preparation, more
					© with variable performance for technologies;	information via email
					efficiency, investment costs, etc. can vary	to MStadler@lbl.gov
					over time and model technology	
					breakthroughs and advancements	

1.1.0.w	I&P	April 2012	research	det	 based on 3.9.4 from above, but with 12 typical week profiles to better model load shifting between week days and weekend days 	
2.0.0.w	I&P	Sept 2013	research	det	 based on 1.1.0.w, but with multiple year optimization horizon which optimizes building total energy cost over several years (the number of years is a set that can be modified by the user) has an option that does/does not renew investments (same technologies, same capacities) in installed technologies after the lifetime is reached with linear model for battery degradation (i.e. capacity loss due to ageing) 	
Operations DER-CAM 6.0.0	0	2011	research / comm	det	 basic operations DER-CAM code for scheduling pre-determined DER configurations including the following: electric storage, flow batteries, solar thermal, PV, fuel cell, heat and cold storage, absorption chilling 	http://der.lbl.gov/sites/der.lbl.gov/files/lbnl-4497e.pdf http://der.lbl.gov/sites/der.lbl.gov/files/LBNL%20-%2081939.PDF http://der.lbl.gov/sites/der.lbl.gov/files/LBNL-6127E.pdf
Operations DER-CAM 6.1.0.ev	0	TBD	research / comm	det	 Operations DER-CAM code based on Operations DER-CAM 6.0.0 (see above) with additional modules for charging of EV fleet and determining cost-optimal frequency regulation bid for day-ahead ancillary services market variable time-step 1hr, 15min, 5min 	http://der.lbl.gov/sites/der.lbl.gov/files/lbnl-6154e.pdf
Operations DER-CAM stochastic version 6.1.2.s	Ο	2011	research	stoch	 added stochastic capabilities based on Operations DER-CAM 6.0.0 enabled choice for individual DG technologies to behave deterministically or stochastically added hourly max output parameter to model outages in DG (applied to fuel cell) stationary storage behaves as deterministic to compensate for uncertainty in DG output 	http://der.lbl.gov/public ations/microgrid- reliability-modeling- battery-scheduling- using-stochastic- linear-programming
1.1.0.s	I&P	01 March 2013	research	stoch	 based on 1.1.0.w from above but with 12 typical week profiles to better model load shifting between week days 	http://der.lbl.gov/sites/ der.lbl.gov/files/lbnl- 5937e.pdf

					and weekend days onew electric vehicle fleet management module onew uncertainty in EV driving pattern onew stochastic capabilities enabled	http://gig.lbl.gov/sites/a
2.0.0.s	I&P	spring 2014	research	stoch	 based on 1.0.0.s consideration of uncertainty for wind and PV islanding and microgrid reliability variable time-step 1hr, 15min, 5min 	